



double strikeout) (begin double underline) edge (end double underline) (begin underline) of the circle. (end underline) *The triangle symbol shall contrast with the circle symbol, either light on a dark background or dark on a light background. The circle symbol shall contrast with the door, either light on a dark background or dark on a light background.*

(begin underline) **11B-703.7.2.6.4 Edges and vertices on geometric symbols.** (end underline) ...

**REASON:** DSA-AC is proposing to further amend Section 11B-703.7.2.6.3 based on a comment received during the 45-Day Public Comment Period. The commenter noted that use of the term “inscribed” in place of the term “superimposed” does not fully capture the intent of this section. DSA-AC is proposing to further amend this section by making several non-substantive changes in terminology to clarify the intent of this section. The language “geometrically inscribed on” is being replaced with “superimposed on and geometrically inscribed within”, the language “located no further than ¼ inch maximum” is being replaced with “located ¼ inch maximum”, the term “circumference” is being replaced with the term “edge”. These changes in no way change the regulatory intent of this section, but will provide additional clarity and consistency for code users.

---

## ITEM 11B.51

### DIVISION 8: SPECIAL ROOMS, SPACES, AND ELEMENTS

(begin underline) **11B-812 Electric vehicle charging stations**

**11B-812.7 Access aisle.** ...

**11B-812.7.1 Location.** ...

**11B-812.7.2 Marking.** *Access aisles at vehicle spaces shall be marked with a painted borderline around their perimeter. The area within the borderlines shall be marked with hatched lines a* (end underline) (begin single underline and double strikeout)  (end single underline and double strikeout) (begin double underline)            (end double underline) (begin underline) of 36 inches (914 mm) on center. The color of the borderlines, hatched lines, and letters shall contrast with that of the surface of the access aisle. The blue color required for identification of access aisles for accessible parking shall not be used. Access aisle markings may extend beyond the minimum required length.

**11B-812.7.3 Lettering.** (end underline) ...

**REASON:** DSA-AC is proposing to further amend Section 11B-812.7.2, based on a comment received during the 45-Day Public Comment Period, to correct an inadvertent typographical error. The commenter noted the proposed language of this section was in conflict with the language existing in CBC Section 11B-502.3.3. Specifically, Section 11B-502.3.3 requires access aisles to be marked with hatched lines a *maximum* of 36 inches on center, while proposed Section 11B-812.7.2 would require hatched lines a *minimum* of 36 inches on center. DSA-AC is proposing to further amend this section to be consistent with the existing provisions of the CBC. This change will provide clarity and consistency for code users.

---

## Notation

**Authority:** Government Code Section 4450.

**References:** Government Code Sections 4450 through 4461, 12955.1(c) and 14679; Health and Safety Code Sections 18949.1, 19952 through 19959; and Vehicle Code Section 22511.8.