

IR A-4

GEOHAZARD REPORT REQUIREMENTS: 2016, 2013 CBC

Disciplines: Structural History: Revised 10/07/16 Under 2016 CBC Last Revised 12/19/13 Under Prior CBCs

Original Issue 09/01/99

Division of the State Architect (DSA) documents referenced within this publication are available on the DSA Forms or DSA Publications webpages.

PURPOSE

This Interpretation of Regulations (IR) provides clarification of specific Code requirements relating to the requirements for the submission of a geohazard report to the California Geological Survey (CGS) for acceptance, and, subsequently, to DSA for projects within the iurisdiction of DSA.

SCOPE

This IR is applicable for projects submitted to DSA for review under the 2013 and 2016 editions of the California Building Code (CBC).

BACKGROUND

A geohazard is any geologic condition that is a potential danger to life or property. Geohazards include, but are not limited to, ground shaking, surface rupture, liquefaction, tsunami and landslides.

The California Administrative Code (CAC), Section 4-317(e) includes requirements for the performance of geotechnical (soils) studies and geohazard studies. Note that "Geotechnical Reports" (or soils investigation reports) often include soils studies only and might not include complete geohazard studies.

In addition, CBC Section 1803A describes requirements for engineering geologic reports. supplemental ground-response reports, and geotechnical reports. Any of these reports may contain elements of the geohazard studies, and shall all be submitted to CGS for review.

1. GENERAL PROCEDURE

When a geohazard report is required for a project (see criteria in Section 2 below), the report must be submitted to CGS before the project is submitted to DSA. Final DSA approval will not occur until DSA receives the final acceptance letter from CGS. It is the responsibility of the applicant to provide CGS's acceptance letter to DSA and reference the DSA application number for the project.


If a provisional acceptance letter is issued by CGS, as is often required for projects with ground improvements, see Section 8.

1.1 Submittal to CGS

School districts are responsible for the submittal of the geohazard report to CGS and for the cost of review. Reports should be submitted to CGS approximately two months prior to submittal of the project to DSA; contact CGS for its current review timelines. Instructions are available on

CGS's website: Project Review Frequently Asked Questions.

The geohazard report submittal to CGS shall include a site data report as required by CBC Section 1603A.2.



1.2 Submittal to DSA

A copy of the geohazard report, site data report, and the application to CGS indicating the CGS project number shall be submitted to DSA along with the initial DSA project application.

2. PROJECTS REQUIRING GEOHAZARD REPORTS

A geohazard report shall be submitted to CGS for projects as described below.

2.1 Site Specific Ground Motion Analysis

A geohazard report is required for any project for which a site specific ground motion analysis is required or voluntarily used to develop seismic parameters used for design.

The site specific ground motion analysis requirements of CBC Section 1616A.1.3 (1616.10.2*) and American Society of Civil Engineers (ASCE) 7, Section 11.4.7 are not required for projects delineated in Section 3 as not requiring a geohazard report.

2.2 New Sites

A geohazard report is required for all construction on a new site.

2.3 New Structures on Existing Sites

A geohazard report is required for all new buildings or structures, except as delineated in Section 3.

2.4 Additions

A geohazard report is required for all additions except as delineated in Section 3.

Note: When an addition involves alterations to an existing building, the geohazard reporting requirements of Section 2.5 also apply.

2.5 Alterations to Existing Buildings

A geohazard report is required for alterations which:

- **2.5.1** Involve rehabilitation of a structure as defined per CAC Section 4-307 or 4-309(c).
- 2.5.2 Voluntarily modify the lateral force resisting system (per CAC § 4-309[d]) and include new foundations supporting seismic force resisting systems which utilize any one of the following:
 - Deep foundations.
 - Spread foundations designed for bearing pressures that exceed the maximum recommended foundation soil bearing pressures in an existing geotechnical report for that structure or, when a report is not available, the values set forth in CBC Table 1806A.2.
 - Foundations that are not deformationally compatible with the existing foundations (e.g. adding spread footings to a structure supported on deep foundations).
- 2.5.3 Involves repair of structural earthquake damage per CAC Section 4-309(e).

2.6 New Relocatable Buildings and Relocation of Existing Relocatable Buildings within a Mapped Geologic Hazard Zone

Single-story relocatable buildings located in a mapped geologic hazard zone that are less than 2160 sf on non-permanent foundations will require a geologic hazards report. If the report indicates that there are no geologic hazards at the site that may have potential impact upon the building, DSA may waive the requirement for submittal and approval of the report by CGS.

3. PROJECTS NOT REQUIRING GEOHAZARD REPORTS

For projects on existing sites, with scope limited to one or more of those described in Sections 3.1 through 3.2.3 below, a geohazard report is not required.

3.1 For Any Existing Site, Regardless of Location

3.1.1 Sitework, non-building structures, or structures not intended for human occupancy, unless such construction is essential to the operation of the facility.

*Indicates alternative California Building Code (CBC) sections that community colleges may use per 2013 and 2016 CBC Section 1.9.2.2

 Non-building structures include, but are not limited to, light poles, flag poles, signs, scoreboards, ball walls, fences, and retaining walls. Non-building structures do not include structures that shelter a use or occupancy such as canopies, lunch shelters, or carports.

Exception: Individual fabric shade structure used as shade canopies and lunch shelters of regular shape (e.g. hip, flat, gable, pyramid) 1,600 square feet or less supported on all corners by columns (3 minimum) with maximum column grid spacing of 40 feet do not require a geohazard report. Individual fabric shade structures may be grouped adjacent to each other using common columns up to a maximum of 4,000 square feet combined. All other fabric shade structures, including single or multiple column supports, used as shade canopies and lunch shelters of regular shape up to a maximum of 4,000 square feet do not require a geohazard report provided a geotechnical report indicates that no liquefaction potential exists.

 A "structure for human occupancy" is any structure used or intended for supporting or sheltering any use or occupancy, which is expected to have a human occupancy rate of more than 2,000 person-hours per year - in accordance with Title 14, Division 2, Chapter 8, Subchapter 1, Article 3, Section 3601(e). Structures not intended for human occupancy include structures such as storage buildings not entered by students and teachers for school purposes and do not include structures that shelter a use or occupancy such as canopies, lunch shelters, or carports

Note: Non-building structures "essential to the use of the facility" **do require** the submission of geohazard reports. Such structures include the following:

- Elevated water tanks necessary for fire protection.
- Earth retaining structures when failure of such structures could endanger occupied structures.
- Communications towers serving Risk Category IV (essential services) buildings.
- Other similar structures.
- **3.1.2** Structures not defined as a "School Building" per CAC Section 4-314 and exempt from DSA structural review as indicated in *IR A-22: Construction Projects and Items Exempt from DSA Review* Appendix A.
- **3.1.3** Temporary relocatable or emergency buildings as defined in CAC Section 4-302(b).

3.2 Existing Sites Outside of a Mapped Geologic Hazard Zone

In addition to the project scopes described in Section 3.1.1 through 3.1.3, above, projects on existing sites which are outside of a "mapped geologic hazard zone" (as defined in Section 4 below) are exempt from the requirement to provide a geohazard report if they involve only:

3.2.1 One or more single-story, wood-frame or light-steel frame structures of Type II or V construction, seismically separated into areas of 4,000 square feet or less in covered area.

Such structures may include, but are not limited to, most relocatable buildings and plywood shear wall buildings.

- **3.2.2** Isolated elevator towers serving no more than two levels.
- 3.2.3 Open metal site structures (e.g. structural steel, aluminum, etc.) seismically separated into areas of 4,000 square feet or less in covered area. Such structures may include but are not limited to shade structures, bleachers, canopies, and carports.

4. DEFINITION OF A "MAPPED GEOLOGIC HAZARD ZONE"

A mapped geologic hazard zone includes the following:

- A "Seismic Hazard Zone," as identified by CGS.
- An "Earthquake Fault Zone" as identified by CGS.
- A fault, landslide, liquefaction, tsunami, or other geologic hazard zone defined in the Safety Element of a Local General Plan.

5. RE-USE OF EXISTING GEOHAZARD REPORTS

An existing geohazard report may be used for a new project if the existing report is based on adequate studies (refer to CGS Note 48 for guidance), a reevaluation is made, and the report is found to be currently appropriate. The existing report for the site and the reevaluation must be submitted to CGS for approval for each project.

A reevaluation is not required if **all three** of the following conditions are met:

- The original geohazard report included the scope of construction proposed for the project.
- The applicable building code has not changed since the original report was issued.
- The project is submitted to DSA within the time limit described in the original report.

Note: Subsequent significant geologic events may invalidate an existing Geohazard Report.

6. SCOPE OF GEOHAZARD STUDIES

For guidance in conducting a study and reporting evaluations and recommendations, refer to the following (CGS Publications):

- Special Publication 117A, "Guidelines for Evaluating and Mitigating Seismic Hazards in California (2008)."
- Special Publication 42 (Interim Revision 2007), "Fault-Rupture Hazard Zones in California."

CGS Note 48 will be used as a guide for review by CGS: Geological and Environmental Review.

7. CONTENT OF GEOHAZARD REPORTS

Requirements regarding contents of geohazard reports are addressed by CGS: Geological and **Environmental Review.**

8. REQUIREMENTS FOR SOIL IMPROVEMENT PROJECTS WITH CGS PROVISIONAL **ACCEPTANCE**

If a provisional acceptance letter is issued by CGS, as often required for projects with soil improvements, DSA approval of the construction documents may occur provided the conditions in this Section are complied with. However, foundation construction may not commence until the soil improvements and supplemental testing have been completed, and a final acceptance letter

is issued by CGS and processed by DSA as a deferred submittal.

8.1 Construction Documents Note

The following paragraph shall be placed on the project title sheet:

"The Geotechnical Engineer shall submit a comprehensive report documenting final soil improvements constructed, construction observation, and the results of the confirmation testing and analysis to the California Geological Survey (CGS). The project foundation construction shall not commence until final CGS acceptance letter is issued and processed by DSA as a deferred submittal."

8.2 Deferred Submittal

DSA will process CGS's final acceptance letter as a deferred submittal. The following shall be indicated as a deferred submittal on the construction documents and in eTracker.

"Soil Improvement - CGS Final Acceptance of Geohazard Report"

8.3 Statement of Structural Tests and Special Inspections

The following items shall be added to the form DSA 103: List of Required Structural Tests and Special Instructions under item "6. Other Soils":

TEST OR SPECIAL INSPECTION	TYPE	PERFORMED BY	CODE REFERENCE AND NOTES
a. Soil Improvements	Test	GE	Submit a comprehensive report documenting final soil improvements constructed, construction observation, and the results of the confirmation testing and analysis to CGS for final acceptance.
b. Inspection of Soil Improvements	Continuous	GE	

8.4 DSA eTracker

The following note shall be added to the Plan Check Worksheet "Notes":

"The CGS final acceptance is not issued; Geotechnical engineer shall submit a comprehensive report documenting final soil improvements constructed, construction observation, and the results of the confirmation testing and analysis to CGS for final acceptance prior to foundation construction."

REFERENCES:

California Code of Regulations, Title 24 2016 and 2013 CAC Section 4-317(e) 2016 and 2013 CBC Sections 1603A.2, 1616A, 1616*, and 1803A

This IR is intended for use by DSA staff and by design professionals to promote statewide consistency for review and approval of plans and specifications as well as construction oversight of projects within the jurisdiction of DSA, which includes State of California public schools (K-12), community colleges and state-owned or state-leased essential services buildings. This IR indicates an acceptable method for achieving compliance with applicable codes and regulations, although other methods proposed by design professionals may be considered by DSA.

This IR is subject to revision at any time. Please check DSA's website for currently effective IRs. Only IRs listed on the webpage at www.dgs.ca.gov/dsa/publications at the time of project application submittal to DSA are considered applicable.